



380 Stewart Road Hanover Twp, PA 18706  
 PH: 570-825-1900  
 FAX: 570-825-7108

# Lighthawk LED GEN II

## Specifications:

Power Source: 4 Cell Lithium Ion Battery  
 LED Life: 30,000 Hours  
 Light Output: 300 Lumens High Mode / 125 Lumens Low Mode  
 Peak Beam Intensity: 70,000 Candela  
 Beam Distance: 447 M  
 Battery Run Time: 7 Hours High Mode / 14 Hours Low Mode  
 Impact Rating: 1 Meter  
 Weight: 1.9 lbs (with battery)  
 Length: 9.5 in.  
 Width: 3.12 in.  
 Height: 5.12 in.  
 Operating Temp Range: -20C to 50C

<b>Output</b>  <b>300 LUMENS</b>	<b>Runtime</b>  <b>7H / 14H</b>	<b>Peak Beam Intensity</b>  <b>70,000 CD</b>
<b>Impact Resistance</b>  <b>1m</b>	<b>Beam Distance</b>  <b>447 M</b>	<b>Waterproof</b>  <b>1m</b>

NFPA 1901-14.1.11.2 (2003) Certified Mounted in any Position

## Standard Features:

- Wall and Vehicle Mountable
- Dual Mode Main Beam  
High Mode / Low Mode
- Super Tough Nylon Construction
- LED charge Status Indicator
- Non-Slip rubber bottom and handle
- Low Battery Indicator
- Dual Mode High Visibility Signal Tail Light  
Flashing Mode/ Steady Mode
- Easily adjustable articulated head
- Quick release shoulder strap
- Limited Lifetime warranty



Part #s:	Description
07610	4-cell, Orange, 120V AC
07610 UTIL	4-cell, Orange, 120V AC & 12/24V DC
07630	4-cell, Orange, 12/24V DC
07650	4-cell, Orange, 220V AC
07670	4-cell, Orange, Direct Wire
07612	4-cell, Yellow, 120V AC
07612 UTIL	4-cell, Yellow, 120V AC & 12/24V DC
07632	4-cell, Yellow, 12/24V DC
07652	4-cell, Yellow, 220V AC
07672	4-cell, Yellow, Direct Wire
07611	4-cell, Black, 120V AC
07611 UTIL	4-cell, Black, 120V AC & 12/24V DC
07631	4-cell, Black, 12/24V DC
07651	4-cell, Black, 220V AC
07671	4-cell, Black, Direct Wire

## Safety Certification



Class I, II, III, Division 1, Groups C - G, T1  
 Class I, II, III, Division 2, Groups A - G, T5  
 -20°C to +50°C

Ingress Protection Level: IP67 1 meter

## Accessories Description

9B-1962-1	4-Cell Replacement Lithium-Ion Battery
9B-1963-2	6-Cell Replacement Lithium-Ion Battery
07690	Charger Base
20628	120V AC Adapter
21132	Shoulder strap
21134	Seat Belt Style Strap
20629	220V Euro Cord
07870	12/24V DC Cord
3B-2033	Direct Wire Kit
10B-1926	Magnet Kit
10B-1926-I	Magnet Kit Installed

